

62  
E1  
Coutel

a plurality of linear fold regions, each fold region overlying and defining a corresponding crease line of the packaging laminate, the plurality of linear fold regions having a bond strength less than the first bond strength, wherein when the laminate is folded at the crease lines, the first and second layers separate from one another; and

a liquid-tight coating disposed on the first layer outwardly of the second layer and a liquid-tight coating disposed on the second layer outwardly of the first layer.

---

Please amend claim 27 as follows:

92

SWH  
27. (Amended) A packaging container comprising:

a first layer having a first plurality of linear fold regions, each linear fold region defining a corresponding crease line of the packaging container, the first layer also having a first plurality of non-fold regions;

a second layer coextensive with the first layer, the second layer having a second plurality of linear fold regions, each of the linear fold regions defining a corresponding crease line of the packaging container, the second layer also having a second plurality of non-fold regions,

the first layer first plurality of non-fold regions being bonded to the second layer second plurality of non-fold regions at a first bond strength greater than a bond strength of the first layer first plurality of linear fold regions and the second layer second plurality of linear fold regions, wherein when the bonded first and second layers are folded at the crease lines, the first and second layers separate from one another at the liner fold regions; and

a liquid-tight coating disposed on the first layer outwardly of the second layer and a liquid-tight coating disposed on the second layer outwardly of the first layer.

---